

Op. Rad. (M.)	Bm. Lth. (M.)	16.0	19.0	22.0	25.0	28.0	31.0	34.0	37.0	40.0	43.0	46.0	49.0	52.0	55.0	58.0	61.0	64.0	67.0	70.0	Bm. Lth. (M.)	Op. Rad. (M.)	
4.5		100,000																				4.5	
5.0		100,000	100,000	5.5x 83,000																		5.0	
6.0		76,900	76,800	76,000	6.1x 70,000	6.2x 62,000																6.0	
7.0		59,800	59,600	59,500	59,500	59,000	7.1x 66,000	7.4x 60,000															7.0
8.0		48,700	48,500	48,400	46,400	48,100	48,100	48,000	8.1x 42,000	8.7x 38,600													8.0
9.0		41,000	40,000	40,600	40,600	40,400	40,400	40,000	40,000	38,000	9.2x 34,000	9.7x 30,000											9.0
10.0		35,300	35,200	34,900	34,900	34,800	34,700	34,600	34,600	34,600	32,000	29,600	10.2x 26,500	10.8x 24,000	11.3x 21,000								10.0
12.0		27,500	27,300	27,100	27,100	26,900	26,800	26,800	26,800	26,800	26,600	26,500	24,500	23,000	20,600	19,300	12.3x 17,800	12.8x 15,700	13.4x 14,200				12.0
14.0		22,500	22,300	22,000	22,000	21,800	21,700	21,700	21,600	21,500	21,400	21,400	21,100	21,000	19,200	18,300	17,000	15,300	14,000	13,000			14.0
16.0		15.4x 19,900	18,700	18,500	18,400	18,200	18,100	18,100	17,900	17,900	17,800	17,800	17,600	17,500	17,500	17,300	16,000	14,400	13,500	12,500			16.0
18.0			16,000	15,800	15,700	15,600	15,500	15,500	15,300	15,300	15,100	15,100	15,000	14,900	14,700	14,700	14,600	13,600	13,000	12,000			18.0
20.0				13,900	13,800	13,600	13,400	13,400	13,300	13,200	13,100	13,000	12,900	12,800	12,700	12,600	12,500	12,300	12,200	11,500			20.0
22.0				20.6x 13,400	12,100	11,900	11,800	11,800	11,600	11,600	11,500	11,400	11,200	11,200	11,000	11,000	10,900	10,700	10,600	10,500			22.0
24.0					23.2x 11,300	10,600	10,500	10,400	10,300	10,200	10,200	10,000	10,000	9,800	9,700	9,700	9,600	9,400	9,200	9,200			24.0
26.0						25.8x 9,700	9,400	9,400	9,200	9,100	9,000	8,900	8,800	8,700	8,500	8,500	8,400	8,200	8,200	8,100			26.0
28.0							8,500	8,500	8,300	8,200	8,100	8,000	7,900	7,800	7,600	7,600	7,500	7,300	7,200	7,100			28.0
30.0							28.4x 8,300	7,700	7,500	7,400	7,300	7,200	7,000	7,000	6,800	6,700	6,700	6,400	6,400	6,400			30.0
32.0								31.0x 7,300	6,800	6,700	6,600	6,500	6,400	6,400	6,100	6,100	6,100	5,800	5,700	5,600			32.0
34.0									33.6x 6,400	6,200	6,100	5,900	5,800	5,700	5,500	5,500	5,400	5,200	5,100	5,000			34.0
36.0										5,700	5,500	5,400	5,200	5,200	5,000	4,900	4,900	4,600	4,600	4,500			36.0
38.0										36.2x 5,600	5,100	4,900	4,800	4,700	4,500	4,500	4,400	4,200	4,100	4,000			38.0
40.0											38.8x 4,900	4,600	4,400	4,300	4,100	4,100	3,900	3,700	3,600	3,500			40.0
42.0												41.4x 4,300	4,000	3,900	3,700	3,600	3,500	3,300	3,100	3,000			42.0
44.0													3,700	3,500	3,300	3,200	3,100	2,900	2,700	2,600			44.0
46.0														3,200	2,900	2,800	2,700	2,500	2,300	2,200			46.0
48.0														46.6x 3,100	2,600	2,500	2,400	2,100	1,900	1,800			48.0
50.0															47.2x 2,400	2,200	2,100	1,800	1,600				50.0
52.0																51.8x 1,900	1,800	1,600					52.0

- Loads depicted on chart are in kgs
- 5.5 x 83,000 in the chart means that rated load of 83,000 kgs. is at a limiting operating radius of 5.5 M

PCSA Rating:
The rated loads, listed are determined according to PCSA and do not exceed 75% of tipping load on condition that the machine is stationed on firm, level ground



PBL TRANSPORT CORPORATION PVT LTD